


Model	Line	Standard
VEGA	HORIZON	EN ISO 20345:2011
Article	Protection	Availability in stock
52045-02L	S3 SRC	AVAILABLE 



Sole

PU Dual-Density SRC passed
Two-component PU sole with self-cleaning pattern, extremely flexible for various places of use, both indoor and outdoor, with SRC Antislip Standard.

Removable insole



Antistatic absorbent in foamed latex insole

Protection elements



STEELPROTECTION

Steel toecap, with anti-corrosion paint. Protection of over 200J. Comfortable fit, with compensation rubber. Stainless steel foil with acid-resistant paint.


Type	Ankle boot	
Upper	Pigmented Leather-Hydrotech Reflex insert Coagulated PU	
Lining	3D Air circulation 320 gr.	
Anti-slip Lining		
Removable insole	Absorbent in foamed latex insole	
Sole	PU Dual-Density SRC passed	
Toe cap	STEEL PROTECTION	
Antiperforation		
Size	36-48	Weight gr. 650
Features		

Working environment

Multipurpose, Building, Engineering, Farming and Gardening

SRC

SRC (SRA+SRB)



SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32	0.42
	HEEL (center of heel) ≥ 0.28	
SRB STEEL + GLYCEROL	FLAT ≥ 0.18	0.19
	HEEL (center of heel) ≥ 0.13	

Sole 52-53
PU - PU

EN ISO 20345:2011

Antistatic

EN ISO 20345:2011 6.2.2.2.

0,1 < MΩ < 1000

ANTI-STATIC SHOE

Plus



Plus

Thermoformed heel counter in a special material, to support the ankle.

STEELPROTECTION DUALMICRO DRIFTWICBO Reflex inserts SPUNTERBO PHTHALATEFREE



Symbols

